

# MIL docking station V110

For GETAC V110 Convertible Notebook

## Technical data

- ▶ Type: Active docking station for holding a "Getac V100 G7 Convertible Notebook"
- ▶ Housing design and color: Aluminum, powder-coated, RAL 7013
- ▶ Locking: 2 x clamping lock with snap-in function, on the side
- ▶ Dimension: Approx. 355 mm x 240 mm x 72 mm (without tray and latch)
- ▶ Mounting bracket: Prepared for VESA100 mount
- ▶ Weight: 4.3 kg
- ▶ Power supply: DC-In: 19V ±10 %
- ▶ Power consumption: Max. 66.5 watts with active tablet charging function
- ▶ Features & interfaces
  - > 1 x Ethernet, 10/100/1000BASE-T, on MIL connector Amphenol Socapex
  - > 2 x USB 3.0, on 2 x MIL connectors Amphenol Socapex
  - > 2 x serial interface, on 2x MIL connectors Amphenol D-Sub (MIL-24308)
  - > 1 x DC Power In, on MIL connector SJT series, 3-pin
- ▶ Environmental requirements
  - > Protection class: IP 67
  - > Ambient temperature during operation: -29°C ... 63°C
  - > Ambient temperature without operation: -51°C ... 71°C
  - > Humidity: 5 ... 95% (at 25°C ambient temperature, non-condensing)
  - > Continuous operation: 24/7



## Certification and quality management

Especially in the security-relevant defense sector, the know-how about required standards and certifications is crucial. We develop in line with requirements, test and certify the end product or provide support until certification is complete.



[iesy.com/en](https://iesy.com/en)